



**SAFETY SYSTEM®**  
WORKERS PROTECTOR

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

**TECHNICAL SHEET**

**export@sirsafety.com**  
**www.sirsafety.com**

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED  
= ISO 9001 =

<b>Name: Jump Low Shoe</b>	<b>Code: 22008</b>	<b>MB18 CALZATURE SERIE TOTAL PLANE</b>
----------------------------	--------------------	---

**Description**

Low shoe with 200 joule composite toecap and Zero Penetration composite midsole. Highly breathable Mesh fabric upper, reflex inserts and eco-friendly leather overcap. Metal Free.  
REACTOR sole: Polyurethane/TPU sole. The open-cell polyurethane (PU) insole allows for a high shape memory effect and provides a cushioning effect. The TPU outsole provides flexibility, softness, as well as mechanical and chemical resistance. Especially after prolonged use, it enhances forefoot flexibility for a more natural motion, reducing fatigue. Anti-slip SRC standard.  
DUAL FRESH Insoles in bi-component fabric with variable thickness and shock-absorbing properties. They are made from special foams and particularly contact-friendly fabrics which prevent perspiration.  
DRY-PLUS polyester lining offering superb absorbing properties prevents feet overheating.



**Main features:**

- Conforming the German standard BGR 191, suitable for use of orthopaedic insoles.
- Curved sole to facilitate grip and walking
- Innovative design
- Total support of the outsole on the ground
- Open angles to help releasing the impurities
- Outsole with high memory performance
- Outsole in TPU, resistant to oils and hydrocarbons
- Grooves with open angles to discharge any accumulation
- Horizontal grooves to improve flexibility and movements
- Outsole in high mechanical resistance and long-lasting TPU
- Grooves pattern for better draining of liquids
- Anti-slip SRC standard

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of European standards EN ISO 20345. It is classified as PPE Cat. II.

Category <b>II</b>	Colours Black-Grey	Available Sizes 39-47
Quantity/Carton <b>10</b>	Important Information The footwear should be stored in a cool dry place, far from heat sources and direct light. Make sure footwear is in good condition, before use. If the shoes are damaged, replace them.	Recommended for Industrial plants, Construction and Road Work Sites, Logistics and Handling.
Dexterity	EC Standards EN ISO 20345  Safety Class: S1P SRC	Storage and cleaning Clean the footwear with a soft brush and water.