



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy

Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED

Name: Seta Ultra Light Shoe

Code: 25021

MB20 CALZATURE SERIE NEW ULTRA LIGHT

Description

It features Eva midsole, with 200 joule composite toecap and Zero Penetration textile midsole.

Cutting-edge seamless upper in nylon. S1P.

Outer sole in nitrile rubber with TPU anti-twist stabilizers, which guarantee a high grip, according to SRC slipping resistant performance.

EVA midsole for an antishock effect and unprecedented lightness, with anti-weariness properties.

Preformed inner sole with back support, for an enhanced shock absorber

3D-TEX LINING for foot ventilation, reducing perspiration.

Main features:

- Ultralight shoe, amongst the lightest on the market
- More comfort, flexibility, lightweight and breathability.
- Low profile cleats, does not accumulate debris
- Reinforcement overcap in synthetic material
- Multitraction design, grip on any surface
- High resistance nitrile rubber outsole
- EVA antishock insole
- TPU anti-twist stabiliser
- Surface with self-cleaning inserts

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of European standards EN ISO 20345. It is classified as PPE Cat. II.



Category	Colours	Available Sizes
II	Black/Orange	36-47
Quantity/Carton	Important Information	Recommended for
10	The footwear should be stored in a cool dry place, far from heat sources and direct light. Make sure footwear is in good condition, before use. If the shoes are damaged, replace them.	Indoor activities.
Dexterity	EC Standards	Storage and cleaning
	EN ISO 20345	Clean the footwear with a soft brush and water.
	Safety Class: S1P SRC	