



THE GLOBAL BENCHMARK
FOR QUALITY, SAFETY,
AND DESIGN.

SUPERPLASMA HP



STANDARD

EN 14052



EN 12492

for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral
impact, 4.2.1.4 rear impact

EN 397 | LD

for the following clauses only:
5.1.1 | Shock absorption
5.1.2 | Penetration resistance



MATERIAL

EXTERNAL SHELL:
ABS

INTERNAL SHELL:
HD Expanded Polystyrene

HEADBAND:
Soft PA Nylon



TEMPERATURE OF USE

-10°C / +50°C



WEIGHT

450 g



SIZE

Universal-adjustable from 51 to 63 cm



CATEGORY

II



WHE00106

○ 201

TECHNOLOGIES

- **QUICK FIT SYSTEM** Size adjustment system for maximum stability.
- **2DRY LINER** Moisture-wicking fabric technology for all-day comfort.
- **VENTILATION CHANNELS** 10 air intakes that enhance breathability and comfort.
- **RING TO HOOK** Chinstrap loop that securely attaches helmet to a harness.
- **EARMUFF ADAPTER ATTACHMENT POINTS** For adapters to secure earmuffs.
- **VISOR ATTACHMENT POINTS** For securing KASK eye protection accessories.
- **INTEGRATED LAMP CLIPS** 4 built-in, nylon lamp attachment points.

PRODUCT OF ITALY

3

YEARS
GUARANTEE

10

YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION